




CIXI WANJIE ELECTRONIC CO., LTD

THE SPEC SHEET



Electrical

Standard	UL	IEC
Rated voltage	600V	450V
Rated current	20A	32A
Contact resistance	20m Ω	
Insulation resistance	500M Ω /DC500V	
Wire range	20~12AWG 0.5~4.0mm ²	
With standing voltage	AC 2000V/1 Min	

Mechanical

Torque	0.4Nm(3.6Lb.in)
Temp.Range	-40°C~+105°C

Dimensions

Pitch	8.2mm
Poles	12p

Material

Housing	PA66, UL94V-2
Screws	M2.5 Steel Zn plated
Pressure line column	SPCC Zn plated

linear dimension(Tolerances Standard GB/T 14486-2008)		\equiv	-	\square	//	\perp										
variable range	to 6	over 6 to 10	over 10 to 18	over 18 to 30	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 160	over 160 to 200	over 200 to 250	all	to 5	over 5 to 30	over 30 to 120	over 120 to	
tolerance	± 0.1	± 0.14	± 0.19	± 0.25	± 0.32	± 0.45	± 0.57	± 0.72	± 0.88	± 1.05	± 1.25	0.5	0.025	0.06	0.12	0.4

UNITS	mm	SIZE	A4	SCALE	3:2	THIRD ANGLE PROJECTION	
CIXI WANJIE ELECTRONIC CO., LTD							
						TITLE	MY8HS-8.2-1YY-00A